

AMI Hydrazine

*On-line Analyzer and Controller
for Hydrazine and Carbohydrazide
used as Boiler Feedwater Oxygen
Scavengers*

- *Measuring range: 0.1 to 600 ppb.*
- *Automatic temperature compensation.*
- *Maintenance-free self-cleaning 3-electrode system.*
- *Monitoring of sample flow and cleaning efficiency.*
- *Alarm in case of insufficient sample flow.*
- *Mounted on a stainless steel panel.*
- *Factory tested, and ready for installation and operation.*

Data Sheet No: DenA26541X0X0



Hydrazine and Carbohydrazide

Hydrazine and Carbohydrazide



Analytical System

- Measurement range:
0.1 to 600 ppb
- Stability:
 $\pm 5\%$ of reading per month or ± 2 ppb
- Maintenance-free 3-electrode system.
- Automatic cleaning of sensor surfaces.

AMI Electronic Unit

- Rugged aluminum housing (IP66).
- Two freely scalable current signal outputs (0/4-20 mA), third one as an option.
- Optional fieldbus communication board (Profibus, Modbus, Webserver).

Flow-Cell

- Flow cell made of acrylic glass with flow adjustment valve, digital sample flow monitor and integrated temperature probe.
- Overflow cell for constant flow.
- Sample alkalization with highly efficient diisopropylamine.

PROFI
BUS

CE

swan

ANALYTICAL INSTRUMENTS